# ZEON XD

## THE NEXT GENERATION PREMIUM WINCH




Redesigned and retooled from the ground up for ultimate performance and durability– ZEON XD is there for the times it just has to work, in all conditions. And with the industry's best warranty, fastest line-speed, and most robust waterproof sealing, ZEON XD is the ultra-reliable recovery tool you can count on when you need it most.

**110010 ZEON XD 10-S**
with 100' of 3/8" Spydura synthetic rope

**110012 ZEON XD 12-S**
with 80' of 3/8" Spydura Pro synthetic rope

- Engineered, tested, and assembled in Clackamas, Oregon, USA.
- New high-performance, high-efficiency motor and geartrain delivers blazing fast no-load line speeds of up to 40 ft/min– the fastest in its class.
- Reliable waterproof construction features o-ring rubber sealing. The entire winch is IP68 submersion and IP69K high pressure spray rated.
- Upgraded, corrosion resistant black fasteners and new, UV resistant bus bar covers meet the highest OEM-grade specifications.
- Full metal armor protects components from impact and damage.
- WARN Spydura synthetic rope is strong, lightweight, easy-to-handle, with heat-resistant inner wraps and abrasion sleeve.
- Upgraded black aluminum fairlead is made of forged aluminum, giving superior corrosion, impact, salt, weather, and UV-resistance for long-lasting good looks.
- Albright contactor control and bus bars for the ultimate in electrical reliability and efficiency.
- Available in 10,000 lb. and 12,000 lb. capacities, with synthetic rope, for a variety of trucks, Jeeps, and SUVs
- Includes a durable waterproof corded remote with 12' lead, and the HUB receiver for 100'+ range of wireless control, when paired with the WARN HUB app
- Industry-leading warranty: Limited lifetime mechanical, seven year electrical–all backed by a global service network.







*HUB Wireless Receiver included (phone not included)*

# ZEON XD is for those who push the limits. It's loaded with the performance features off-roaders need, and the rugged durability they want.

### HIGH-PERFORMANCE, HIGH SPEED

WARN's next-generation motor and geartrain work together to deliver a blazing fast no-load line speed of up to 40 ft/min—the fastest in its class.

### LOW AMPS, HIGH POWER


OEM-grade bus bars provide highly efficient electrical connections, eliminating the exposed, inefficient wiring.

### CONTROLS YOU CAN RELY ON

Power is nothing without control. At the heart of the control pack is the Albright electrical contactor—proven to be the most durable and reliable winch control available.

### SUPERIOR GEAR TRAIN

The heavy-duty three-stage planetary gear train is quieter and more efficient than ever, reducing component strain to give you improved durability.




### WATERPROOF CONSTRUCTION

Features durable O-ring rubber gaskets. This new sealing delivers a longer service life, and meets the most stringent IP68 submersion and IP69K spray testing.

### DURABLE, OEM-GRADE HARDWARE

Improved corrosion resistant black fasteners along with improved, UV resistant bus bar covers meet the highest OEM specifications.

### BLACK ALUMINUM FAIRLEAD

Made of forged aluminum, giving superior corrosion, impact, salt, weather, and UV-resistance for long-lasting good looks.

### BEST-IN-CLASS LOAD-HOLDING BRAKE

The powerful, six-segment cone brake holds the full rated load, and provides superior control while winching.


### LARGE-DIAMETER ALUMINUM-ALLOY DRUM

Larger radius drum creates less stress on the rope, extending it's life. A unique through-drum attachment method is the strongest anchor on the market, and allows for easy rope replacement.

## FEATURES/SPECIFICATIONS

| | ZEON XD 10-S | ZEON XD 12-S |
|---|---|---|
| **Part numbers:** | 110010 | 110012 |
| **Rated line pull:** | 10,000 lbs. (4536 kg) single-line | 12,000 lbs. (5443 kg) single-line |
| **No load line speed:** | 40 ft/min | 31 ft/min |
| **Rated load line speed:** | 5 ft/min | 3 ft/min |
| **No load motor current:** | 64 Amps | 67 Amps |
| **Rated load motor current:** | 458 Amps | 466 Amps |
| **Motor:** | 12V DC, series wound (exclusive WARN high-performance design) | |
| **Electrical controls:** | Albright Contactor | |
| **Wiring:** | Automotive OE-grade bus bars | |
| **Corrosion resistance:** | 408 hour salt spray | |
| **Ingress protection:** | IP68 submersion and IP69K spray testing | |
| **Remote Control:** | Remote switch, 12' (3.7m) lead, plus HUB Wireless Receiver | |
| **Geartrain:** | 3-stage planetary | |
| **Gear ratio:** | 141:1 | 176:1 |
| **Clutch (freespooling):** | Rotating ring gear with stainless steel clutch lever. Manual lever operation. | |
| **Brake:** | Automatic, six segment mechanical cone | |
| **Drum diameter/Length:** | 3.15"/9.0" (80mm/229mm) | |
| **Rope:** | 3/8" x 100' (9.52mm x 30m) Spydura synthetic | 3/8" X 80' (9.52mm x 24.38m) Spydura Pro Synthetic |
| **Fairlead:** | Black anodized, forged aluminum hawse | |
| **Recommended Battery:** | 650 CCA minimum for winching | |
| **Battery leads:** | 2 gauge, 72" (1.83m) | |
| **Finish:** | Satin-black powder coat | |
| **Weight:** | 70 lbs. (32 kg) | |
| **Final point of assembly:** | Warn facility in Clackamas, Oregon, USA | |
| **Warranty:** | Limited lifetime mechanical, 7 years electrical | |

## ZEON XD DIMENSIONS




| | |
|---|---|
| Ⓐ 23.89" (606.7mm) | Ⓔ 10.00" (254.0mm) |
| Ⓑ 10.52" (267.2mm) | Ⓕ 6.94" (176.3mm) |
| Ⓒ 7.78" (197.7mm) | Ⓖ 3.15" (80.0mm) |
| Ⓓ 6.94" (176.3mm) | |

Mounting bolt pattern: 10.0" x 4.5" (254.0mm x 114.3mm)


Warn Industries, Inc.
12900 S.E. Capps Road,
Clackamas, OR USA 97015
**www.warn.com**

Customer Service (North America) 1-800-543-9276
International Sales Support +1 503 722 1200