

**CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2263 & 2264**

**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

|                           |                  |                  |
|---------------------------|------------------|------------------|
| Duration at .006" Lift:   | Intake 308°      | Exhaust 315°     |
| Duration at .050" Lift:   | Intake 248°      | Exhaust 256°     |
| Lift at cam:              | Intake .371"     | Exhaust .381"    |
| Lift at valve:            | Intake .632"     | Exhaust .648"    |
| Timing at .050 Lift: Open | Close            |                  |
| Intake                    | 14.5° BTDC       | 53.5° ABDC       |
| Exhaust                   | 62.5° BBDC       | 13.5° ATDC       |
| Centerlines:              | Int. 109.5° ATDC | Exh. 114.5° BTDC |
| Lobe Separation:          | 112°             |                  |

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264  
Rev. 9/30/15 - QT/mc

©2015 Edelbrock LLC  
Brochure #63-2263C

**CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2263 & 2264**

**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

|                           |                  |                  |
|---------------------------|------------------|------------------|
| Duration at .006" Lift:   | Intake 308°      | Exhaust 315°     |
| Duration at .050" Lift:   | Intake 248°      | Exhaust 256°     |
| Lift at cam:              | Intake .371"     | Exhaust .381"    |
| Lift at valve:            | Intake .632"     | Exhaust .648"    |
| Timing at .050 Lift: Open | Close            |                  |
| Intake                    | 14.5° BTDC       | 53.5° ABDC       |
| Exhaust                   | 62.5° BBDC       | 13.5° ATDC       |
| Centerlines:              | Int. 109.5° ATDC | Exh. 114.5° BTDC |
| Lobe Separation:          | 112°             |                  |

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264  
Rev. 9/30/15 - QT/mc

©2015 Edelbrock LLC  
Brochure #63-2263C

**CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2263 & 2264**

**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

|                           |                  |                  |
|---------------------------|------------------|------------------|
| Duration at .006" Lift:   | Intake 308°      | Exhaust 315°     |
| Duration at .050" Lift:   | Intake 248°      | Exhaust 256°     |
| Lift at cam:              | Intake .371"     | Exhaust .381"    |
| Lift at valve:            | Intake .632"     | Exhaust .648"    |
| Timing at .050 Lift: Open | Close            |                  |
| Intake                    | 14.5° BTDC       | 53.5° ABDC       |
| Exhaust                   | 62.5° BBDC       | 13.5° ATDC       |
| Centerlines:              | Int. 109.5° ATDC | Exh. 114.5° BTDC |
| Lobe Separation:          | 112°             |                  |

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264  
Rev. 9/30/15 - QT/mc

©2015 Edelbrock LLC  
Brochure #63-2263C

**CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2263 & 2264**

**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

|                           |                  |                  |
|---------------------------|------------------|------------------|
| Duration at .006" Lift:   | Intake 308°      | Exhaust 315°     |
| Duration at .050" Lift:   | Intake 248°      | Exhaust 256°     |
| Lift at cam:              | Intake .371"     | Exhaust .381"    |
| Lift at valve:            | Intake .632"     | Exhaust .648"    |
| Timing at .050 Lift: Open | Close            |                  |
| Intake                    | 14.5° BTDC       | 53.5° ABDC       |
| Exhaust                   | 62.5° BBDC       | 13.5° ATDC       |
| Centerlines:              | Int. 109.5° ATDC | Exh. 114.5° BTDC |
| Lobe Separation:          | 112°             |                  |

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264  
Rev. 9/30/15 - QT/mc

©2015 Edelbrock LLC  
Brochure #63-2263C