Product information

PI 33/03/02/2021

Brake Anti-Squeal Paste

Description

A synthetic based specialty with a solid agent to prevent and eliminate noise from brake pads. It is extremely adhesive and high temperature resistant, it resists road salt and water wash-out. With excellent corrosion protection and particularly suited for use with aluminum and magnesium materials as well as on vehicles with ABS/ESP systems.



Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- extremely adherent
- ideally suited as a separating paste

Technical data

Form	pastös, flüssig / pastelike,liquid
Color / appearance	blau / blue
Base	synthetische u. keramische Wirkstoffe
Operating temperature range	-40 bis 392 kurzfristig bis 482 / -40 to 392 short term 482 °F als Schmierpaste / as lubricating agent
	-40 bis 2192 / -40 to 2192 °F als Trennpaste / as release agent
Flash point	>410 °F
Odor	schwach / slightly
Shelf life in original sealed container	24 months

Areas of application

Suitable for use in most common disk brake systems. Must never be applied to the friction surface of the brake disc / brake pads.

Application

Clean the surfaces thoroughly before use and then apply to the back of the brake pad and to the contact surfaces and fasteners. Do not apply on friction surfaces!

Comment

Do not under any circumstances allow Brake Anti-Squeal Paste to get onto the friction surface of the brake lining or the brake disc.

part no. 20240: ⚠ **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

200 ml Can aerosol	20240 USA (-EN-)
250 g Brush-in-cap can sheet metal	22092 USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de