R-SERIES

POWERSPORTS WINCHES

STARTING AT: $279.99



NOW AVAILABLE IN CAPACITIES UP TO 6,000 LBS.

WARN ENGINEERED, TESTED, AND PROVEN

WARN R-Series Powersports Winches offer reliable performance from a name you can trust. With capacities ranging from 2,500 lbs. to 6,000 lbs.—our highest capacity powersports winch ever—we offer something for every ATV, UTV, or even something as small as a pickup or SUV. R-Series has the features you want, the power you need, and a price that won't leave you stuck looking at lesser brands.

Engineered in-house at our Oregon headquarters, these winches are built to Warn's specs and put through rigorous testing and quality control measures. All-metal gear trains, IP67 waterproofing, a compact design, and steel or synthetic rope make R-Series the top standard-duty powersports winches on the market. After all, if they're going to wear a red WARN W, they must be better than good, they need to be great.

KEY FEATURES:

- **BACKED BY WARN:** Engineered in Oregon, built to WARN specs, and thoroughly tested for quality control
- **WATERPROOF:** IP67 waterproofing keeps the water, dirt, and debris out and reliability in
- **DURABLE:** Highly efficient and strong all-metal three-stage planetary gear train is built to last
- **COMPACT DESIGN:** Easy to install
- **RELIABLE BRAKE:** Automatic load-holding brake for excellent control
- **SUPERIOR WARRANTY:** 5-year mechanical warranty, 3-year electrical warranty, supported by a US-based customer service team

R-SERIES LINEUP



R25 WINCH: Equipped with 50' of 3/16" steel rope, roller fairlead, handlebar-mounted rocker control switch. **110025**



R25-S WINCH: Equipped with 50' of 3/16" synthetic rope, hawse fairlead, handlebar-mounted rocker switch. **110020**



R35 WINCH: Equipped with 50' of 7/32" steel rope, roller fairlead, handlebar-mounted rocker switch, and dash-mounted control switch. **110035**



R35-S WINCH: Equipped with 50' of 7/32" synthetic rope, hawse fairlead, handlebar-mounted rocker switch, and dash-mounted control switch. **110030**



R45 WINCH: Equipped with 50' of 1/4" steel rope, roller fairlead, corded remote, and dash-mounted control switch. **110045**



R45-S WINCH: Equipped with 50' of 1/4" synthetic rope, hawse fairlead, corded remote, and dash-mounted control switch. **110040**



R60-S WINCH: Equipped with 50' of 1/4" synthetic rope, hawse fairlead, corded remote, and dash-mounted control switch. **110060**

WARN®

WARN.COM

Customer Service: 1-800-543-9276

R25, R25-S SPECIFICATIONS

Part number: 110025 (R25), 110020 (R25-S)
Rated line pull: 2,500lbs (1134kg) single-line
Motor: 12V DC permanent magnet
Sealing: IP67 rated waterproof
Gear train: Differential planetary
Fasteners: Zinc plated
Rope: R25: 50' x 3/16" (15m x 4.8mm) steel, R25-S: 50' x 3/16" (15m x 4.8mm) synthetic
Hook: Zinc plated
Fairlead: R25: Roller fairlead, R25-S: Cast aluminum hawse
Primary control: Handle-bar mounted rocker switch
Remote control: Sold Separately
Brake: Dynamic brake
Warranty: 5 years mechanical, 3 years electrical
Dimensions: length: 12.4" (315mm), height: 4.5" (114mm), width: 4.0" (102mm)
Mounting Bolt Pattern: 3" x 4.9" (76.2mm x 167.4mm)

R35, R35-S SPECIFICATIONS

Part number: 110035 (R35), 110030 (R35-S)
Rated line pull: 3,500lbs (1588kg) single-line
Motor: 12V DC permanent magnet
Sealing: IP67 rated waterproof
Gear train: 3-stage planetary
Fasteners: Zinc plated
Rope: R35: 50' x 3/16" (15m x 4.8mm) steel, R35-S: 50' x 3/16" (15m x 4.8mm) synthetic
Hook: Zinc plated
Fairlead: R35: Roller fairlead, R35-S: Cast aluminum hawse
Primary control: Handle-bar mounted rocker switch; Dash-mounted rocker switch; remote socket harness
Remote control: Sold Separately
Brake: Mechanical brake
Warranty: 5 years mechanical, 3 years electrical
Dimensions: length: 12.3" (312mm), height: 4.7" (120mm), width: 4.6" (117mm)
Mounting Bolt Pattern: 3" x 4.9" (76.2mm x 167.4mm)

R45, R45-S SPECIFICATIONS

Part number: 110045 (R45), 110040 (R45-S)
Rated line pull: 4,500lbs (2041kg) single-line
Motor: 12V DC permanent magnet
Sealing: IP67 rated waterproof
Gear train: 3-stage planetary
Fasteners: Zinc plated
Rope: R45: 50' x 1/4" (15m x 6.3mm) steel, R45-S: 50' x 1/4" (15m x 6.3mm) synthetic
Hook: Zinc plated
Fairlead: R45: Roller fairlead, R45-S: Cast aluminum hawse
Primary control: Dash-mounted rocker switch
Remote control: Hand-held corded remote included
Brake: Mechanical brake
Warranty: 5 years mechanical, 3 years electrical
Dimensions: length: 14.6" (371mm), height: 4.7" (120mm), width: 4.6" (117mm)
Mounting Bolt Pattern: 3" x 6.59" (76.2mm x 167.4mm)

R60-S SPECIFICATIONS

Part number: 110060 (R60-S)
Rated line pull: 6,000lbs (2722kg) single-line
Motor: 12V DC permanent magnet
Sealing: IP67 rated waterproof
Gear train: 3-stage planetary
Fasteners: Zinc plated
Rope: 50' x 1/4" (15m x 6.3mm) synthetic
Hook: Zinc plated
Fairlead: Cast aluminum hawse
Primary control: Dash-mounted rocker switch
Remote control: Hand-held corded remote included
Brake: Mechanical brake
Warranty: 5 years mechanical, 3 years electrical
Dimensions: length: 14.1" (358mm), height: 4.7" (120mm), width: 4.6" (117mm)
Mounting Bolt Pattern: 3" x 6.59" (76.2mm x 167.4mm)