

MODEL 4160 SPECIFICATIONS

199R8179-1

Carburetor Number	Primary Dry Float Setting	Secondary Dry Float Setting	Pump Cam Position	Choke Qualify Adjustment	Choke Index Setting
R1732, R1733, R1734, R1736, R1737	13/64"	3/4"	#1		1 NR
R1737-1	1/2"	3/4"	#1		1 NR
R1738-1, R1740-1			#1		2 NR
R1740A	13/16"	1/2"	#1		1 NR
R1847, R1848, -1, R1849, R1850, R2112, R2142, -1, R2143, R2328, R2599, R2652, -1, R2804, R3113, R3115, R3489, R3490, R3491, R3492, R3602, -1, R4005, R4006, R4473, R81850			#1		INDEX
R1850-1, -2, -3, R2805, R2929, R3116, R3139, -1, R3140, R3301, R3310-2, -3, R3360, R3361, R3394, -1, R3411, R4224, R4235, R4236, R4239, R4397, R4577, R4604, R6299-1, R83310, R83311, R83312, R9015			#1		
R1971, R2052, R3916, R4581, R8159, R9776			#2		
R2143-1	1/2"	3/4"	#1		INDEX
R2973, R3085	7/16"	9/16"	#1		
R3140-1, R3230, R3267, R3268, R3370, R3420, R3605, R3606, R3608, R6444, -1, -2, R6777, -1			#1	.175"	
R3201, R3202, R3203, R4699			#1		1 NL
R3300, R3410	1/2"	5/8"	#1		3 NL
R3667			#2	.175"	
R3391			#1		1 NL
R3575, -1, -2	15/64"	17/64"	#1	.260"	
R3609			#1	.200"	
R3667, -1, -2	15/64"	17/64"	#1	.200"	
R3810	5/16"	11/32"	#1	.190"	
R3814, R3815, R3836, R3837, R3838	5/16"	11/32"	#1	.175"	
R3839	11/32"	11/32"	#1	.200"	
R3916-1	7/16"	9/16"	#1		
R3918, -1, -2, -3, R4749	15/64"	17/64"	#1	.280"	
R4166, -1, -2, -3, R4735, R4440, 1-, -2, -3	15/64"	17/64"	#1	.205"	
R4201, R4202			#1		3 NL
R4217	15/64"	17/64"	#1	.170"	
R4217-1, -2, -3, -4, R4736, -1, -2, R4738, -1, -2,	15/64"	17/64"	#1	.420"	
R4218, R4360	15/64"	17/64"	#1	.080"	
R4218-1, -2, -3, -4, R4360-1, -2, -3, R4366, -1, R4368, -1, -2, R4369, -1, -2, R4737, -1, -2, R4739, -1, -2	15/64"	17/64"	#1	.080"	
R4452			#2	.106"	1 NL
R4552-1, R7985, R7986, R8007, R8123, R8181, R9834, -1, -2, R89834A			#2	.159"	INDEX
R4548			#2	.159"	1 NR
R4549, R6591, R7053			#1	.230"	3 NR

MODEL 4160 SPECIFICATIONS

199RR8179-1

<u>Carburetor Number</u>	<u>Primary Dry Float Setting</u>	<u>Secondary Dry Float Setting</u>	<u>Pump Cam Position</u>	<u>Choke Qualify Adjustment</u>	<u>Choke Index Setting</u>
R4550			#1	.230"	
R4550-1			#1	.035"	1 NR
R4608, R8026			#2		INDEX
R4668	7/64"	9/32"	#1	.195"	
R4668-1	15/64"	17/64"	#1	.195"	
R4734	7/64"	9/32"	#1	.420"	
R4749-1, -2, -3	15/64"	17/64"	#1	.234"	
R6151, R6152, I7159, R9393, R9394, R50148, R50462, R50463, R5046, R80319, R80364AA			#2	.140"	INDEX
R6160, -2, R623, R6255, R6257, R6290, -1	7/64"	13/64"	#1	.195"	
R6191, -1, R613, -1	7/64"	13/64"	#1	.410"	
R6231, R6495			#1	.170"	2 NR
R6252, R6254, R6256	7/64"	13/64"	#1	.340"	
R6267, -1, -2, 17049			#2	.190"	1 NR
R6270, -1, R638	7/64"	13/64"	#1	.234"	
R6291, -1, R619-1, R6829, R6809, R6919, R6979, -1, R6989, R70091, R7010, R7478, R7987			#1	.150"	INDEX
R6407			#2	.140"	3 NL
R6444, -1, R677			#1	.170"	
R6444-3			#1	.155"	
R6515	7/64"	9/32"	#1	.250"	
R6520, R6576, 17413			#2	.221"	4 NR
R6538	7/64"	13/64"	#1	.220"	
R6590, R6730, R6887, R7053-1, R7262, R7850, R8207			#1	.230"	1 NR
R6619			#2	.159"	2 NL
R6729, R6949, -1			#1	.195"	INDEX
R6839, R6946, -1, R66947, R6948, -1			#1	.180"	INDEX
R7009			#2	.159"	4 NR
R7010, R9626			#1	.159"	INDEX
R7128			#2	.140"	
R7163			#1	.140"	
R76446			#2	.201"	1 NL
R7850, R7154, R7974			#2	.090"	INDEX
R8004, R8005, R8006			#2	.190"	1 NL
R8408, R8409, R80341AA			#1	.200"	INDEX
R8410, R8412, R8416, R8589			#1	.200"	2 NR
R8411			#1	.200"	1 NR
R8414			#1	.200"	4 NR

MODEL 4160 SPECIFICATIONS

199RR8179-1

<u>Carburetor Number</u>	<u>Primary Dry Float Setting</u>	<u>Secondary Dry Float Setting</u>	<u>Pump Cam Position</u>	<u>Choke Qualify Adjustment</u>	<u>Choke Index Setting</u>
R8415			#3	.190"	2 NR
R8418, R8419, R8420, R8422			#1	.240"	2 NR
R8590			#1	.221"	INDEX
R9002, R9219			#2	.169"	INDEX
R9013, R9210			#2	.159"	
R9040			#1	.180"	1 NR
R9050			#2	.201"	2 NR
R9051			#2	.200"	1 NR
R9254			#2	.159"	INDEX
R9392, R50412			#1	.120"	INDEX
R9874			#1	.210"	
R50263, R80265			#2	.140"	2 NR
R50399, R50405, R80262			#2	.140"	1 NR
R50419-1, -2, R50469, R80319-1AA			#1	.140"	2 NR
R50464, R50470A, R80318, -1AA			#1	.140"	1 NR
R80265					
R80315			#2	.250"	5 NL
R80383			#1	.228"	3 NL
R80391			#2	.310"	5 NL
R80403			#1	.250"	5 NL