

PRESSURE-TYPE
300V MAX.

U.S. PAT. # 5,113,037
& # 5,151,239

INSTALLING THE KING-2 "ONE-STEP."





IMPORTANT: Turn off power before installing or removing any connectors. Follow applicable electrical codes. ① Strip wires ½". Align conductors. Twist and lead stranded wires slightly. ② Do not pre-twist wire combination. Insert stripped wires through sealant into "One-Step." ③ Hold wires firmly and twist "One-Step" onto wires. Do not over tighten.

Temperature Rating: Use 167°F (75°C). Store 178°F (81°C).

Application: Use up to 300V max. Cu/Cu only. **Do not re-use.**

Listed as a PRESSURE-TYPE wire connector on the following U.L.-Listed & C.S.A.-Approved solid and/or stranded wire combinations:

3 to 5 #20
2 to 4 #18
2 or 3 #16
2 #20 w/2 or 3 #22
3 #20 w/1 or 2 #22
4 #20 w/1 #22
1 #18 w/3 or 4 #22
1 #18 w/2 to 4 #20
2 #18 w/1 to 3 #20 or #22
3 #18 w/1 or 2 #20 or #22
4 #18 w/1 #22
1 #16 w/1 to 4 #20 or #22
1 #16 w/1 or 2 #18
2 #16 w/1 to 3 #22
2 #16 w/1 or 2 #20
2 #16 w/1 #18
1 #14 w/2 to 4 #22
1 #14 w/1 to 3 #20
1 #14 w/1 #16 or #18

Product to be used in accordance with local and national codes
Not to be sold without installation instructions
See your dealer for warranty information
All Trademarks, U.S. & Foreign Patents Pending apply
© 1992 King Technology, Inc. / Printed in U.S.A. 8/92

♻ Package is recyclable.

GF064

KING™

MADE IN U.S.A.

UL SP LISTED 41Y0

KING TECHNOLOGY, INC. 1-800-633-0232, MO (314) 423-5300, FAX (314) 423-2822