Product information

PI 40/26/08/2020

Motorbike 4T SAE 20W-50 Street

Description
High quality mineral-based motor oil for ideal behavior and engine protection in all operating conditions. Provides reliable lubrication, optimum noise suppression and low wear together with perfect clutch function and smooth shifting.



Properties
- mixable with most engine oils
- optimum stability to aging
- outstanding oil film strength
- prevents oil sludge
- very wear resistant
- high shear stability
- especially suitable for wet clutches
- excellent cleaning effect
- tested for the use with catalytic converters
- low evaporation loss
- excellent dispersion properties
- guarantees low oil consumption
- universal application

Specifications and approvals:
API SN PLUS • JASO MA2

Technical data

SAE class (engine oils)	20W-50 SAE J300
Density at 59 °F	0,885 g/cm³ DIN 51757
Viscosity at 104 °F	156 mm²/s ASTM D 7042-04
Viscosity at 212°F	18,00 mm²/s ASTM D 7042-04
Viscosity at 5 °F (CCS)	<= 9500 mPas ASTM D 5293
Viscosity index	128 DIN ISO 2909
Pour point	-27 °F DIN ISO 3016
Evaporation loss (Noack)	7,9 % ASTM D 5800
Flash point	464 °F DIN ISO 2592
Total base number	6,7 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application
For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

Application
Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20062 USA AND CANADA (-EN-F-)
4 l Canister plastic	20064 USA AND CANADA (-EN-F-)
20 l Canister plastic	22116 USA AND CANADA (-EN-F-)
60 l Drum sheet metal	22117 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de