Product information

PI 47/26/02/2021

Special Tec LL SAE 5W-30

Description
Modern, fully synthetic all-season motor oil for superior performance and long engine life. For gasoline and diesel vehicles without particulate filters (GPF/DPF). Exceeds strict test requirements demanded by major manufacturers. Use with extended oil change intervals as per manufacturer.



Properties
- compatible for the use with turbochargers and catalytic converters
- high lubrication reliability
- outstanding engine cleanliness
- optimum stability to aging
- high shear stability
- instant lubrication after cold start
- saves fuel

Specifications and approvals:
ACEA A3 • ACEA B4 • API SL • BMW Longlife-01 • MB-Approval 229.5 • VW 502 00 • VW 505 00

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:
Opel GM-LL-A-025 • Opel GM-LL-B-025

Technical data

Density at 59 °F	0,855 g/cm³ DIN 51757
Viscosity at 104 °F	72,0 mm²/s ASTM D 7042-04
Viscosity at 212°F	12,0 mm²/s ASTM D 7042-04
Viscosity at -31 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -22 °F (CCS)	⩽ 6600 mPas ASTM D5293
Viscosity index	165 DIN ISO 2909
High temperature/high shear viscosity	⩾ 3,5 ASTM D5481
Pour point	-44 °F DIN ISO 3016
Evaporation loss (Noack)	9,5 % CEC L-40-A-93
Flash point	446 °F DIN ISO 2592

Technical data

Total base number	11,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L 3,5 DIN ISO 2049

Areas of application
For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application
Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	2248 USA AND CANADA (-EN-F-)
5 l Canister plastic	2249 USA AND CANADA (-EN-F-)
20 l Canister plastic	20124 USA AND CANADA (-EN-F-)
60 l Drum sheet metal	20364 USA AND CANADA (-EN-F-)
205 l Drum sheet metal	20365 USA AND CANADA (-EN-F-)
1000 l Container	20733 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de