Product information

PI 13/02/03/2021

DIJectron

Description

The unique combination of proven PEA technology and the latest additive generation achieves maximum cleaning performance in the combustion chamber, **in** and **around** the injector tip and in the entire fuel system. Furthermore, DIJectron stops the formation of new deposits so that complex injector systems always work at the highest efficiency. Regular use of DIJectron significantly reduces the risk of engine damage caused by Low Speed Pre Ignition (LSPI), optimizes exhaust gas emissions and protects the fuel system from corrosion.



Properties

- cleans fuel system
- assures precise atomization
- improved driveability
- optimizes fuel consumption and exhaust emissions values
- excellent corrosion protection
- tested for particulate filters and catalytic converters

Areas of application

LIQUI MOLY recommends DIJectron particularly for modern 4-stroke gasoline direct injection (GDI) engines, with or without turbochargers.

Application

Contents (300 mL) is sufficient for 50–70 Liters (13 gal. to 18 gal.) of fuel. For the best results and long term effect add DIJectron to the fuel tank every 4.000 km (2400 miles).

Comment

⚠ **WARNING:** Cancer - www.P65Warnings.ca.gov

Available pack sizes

300 ml Can sheet metal	22076 USA (-EN-)
300 ml Can sheet metal	22110 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de